

# MC150W

X-RAY SOURCE UNIT



**ERAY**  
Electron & Electrical Corp

**Head office** 101-2, 10, Jeongiui-gil, Seongsan-gu, Changwon-si, Republic of Korea 51542

**Branch office** A-2106, 184, Jungbu-daero, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea 17095

**Tel.** +82 70 4288 2202 **Fax** +82 70 7966 2203 **Website** [www.e-ray.co.kr](http://www.e-ray.co.kr)

## SPECIFICATIONS

Parameter	Description/ Value
X-ray tube voltage	40 to 150 kV
X-ray tube current	10 to 500uA
Maximum output	75W
X-ray focal spot size	min 5um
X-ray beam angle	X : +60° -54°, Y : +59° -59°
Focus to object distance(FOD)	13.5mm
Weight	13.5kg
Communication method	RS-232C
Input voltage	DC 24V
Power consumption	Less than 220W
Operating ambient temperature	10~40°C
Storage ambient temperature	0 to 50°C
Operating and storage humidity	20 to 85%
EMC	IEC/EN 61326-1 Emission limits : CISPR 11 Group 1 Class A Immunity requirements : Table 2
Applicable OS	Windows 7, 10
Interface	RS-232C

## DIMENSIONAL OUTLINE (Unit : mm)

